



MOTOROLA

TWO-WAY RADIOS

GM140: The Popular Radio

The Motorola GM140 Professional Radio is a popular choice amongst organisations that require an affordable communication tool for their mobile workforce. The easy-to-use GM140 delivers the fundamental functionality necessary to help ensure that your vehicle-based staff operates efficiently and effectively.



The benefits offered by the GM140 include:

- **Reliability and robustness**
The GM140, like all Motorola two-way radios, has passed the unique Motorola Accelerated Life Test, which simulates 5 years hard use in real-life conditions. Designed for use in extreme operating conditions, the GM140 exceeds the demanding requirements set out in US Military Standards and 1P54 specification.
- **Excellent Audio Quality**
The Motorola X-Pand™ audio enhancement system helps to ensure that voice communications are heard first time, every time, even in noisy working environments
- **Expandability**
The GM140 supports the Motorola PROIS Specification which means that it's fundamental feature set may be enhanced through a range of Motorola, and third-party, plug-in option boards. Examples of the option boards available include:
 - voice storage for message recording, storage and play-back
 - encryption for enhanced security
 - SmarTrunk II for low-cost trunking
- **Ease of use**
The simple push-button operation, combined with easily understood LED indicators, allows your employees to communicate effectively with minimal training. User-friendliness is further enhanced through the use of swappable programmable buttons. This means that those features most valued by your workforce can be programmed to specific buttons labelled with instantly recognised legends.
- **Data capable**
In addition to supporting a range of value-add accessories, the GM140's rear I/O connector provides an interface for third-party terminals, enabling seamless data communications on the move.
- **Fundamental Signalling Capability**
The GM 140 supports the following over-air signalling schemes:
 - Private Line™ (CTCSS) and Digital Private Line™
 - MDC1200
 - DTMF
- **PC Programmable**
Enables your Motorola Authorised Dealer to customise your radios feature set to meet your own specific requirements.

Additional features include:

- PTT-ID
- Channel Scanning
- Busy Channel Lockout
- Monitor Mode
- Repeater Talkaround
- Selective Radio Inhibit

As Dedicated As You Are

Professional Radio

GM140 Mobile Two-Way Radio Specifications

General		
Specification	VHF	UHF
Frequency Range:	136-174 MHz	403-470 MHz
Frequency Stability (-30°C to +60°C, 25CC Ref.)	±2.5 PPM	±2 PPM
Channel Capacity:	4	
Channel Spacing:	12.5/20/25 kHz	
Power Output:	25-45W	25-40W
Power Supply:	13.2Vdc (10.8- 15.6 Vdc) negative vehicle ground	
Dimensions (L x W x H)	177mm x 176mm x 56mm (add 8mm for Volume Knob) (6.97" x 6.93" x 2.2" - add 0.3" for Volume Knob)	
Weight:	1590 g (3.5 lbs)	
Operating Temperature	-30 to 60°C	
Sealing	Passes rain testing to P54	
Shock and Vibration	Meets MIL-STD 810-CD&E and TIA/EIA 603	
Dust	Meets MIL-STD 810-C,D&E and TIA/EIA 603	
Humidity	Meets MIL-STD 810-C,D&E and TIA/EIA 603	

Transmitter	
Specification	VHF/UHF
Modulation Limiting:	±2.5 kHz @ 12.5 kHz ±4.0 kHz @ 20 kHz ±5.0 kHz @ 25 kHz
FM Hum and Noise:	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Conducted/Radiated Emissions:	-36 dBm < 1 GHz -30 dBm > 1 GHz
Adjacent Channel Power	-60dB @ 12.5, -70dB @ 25 kHz
Audio Response: (300 to 3000Hz)	+1, -3dB
Audio Distortion: @ 1000 Hz, 60% Rated Maximum Deviation:	3% Typical

Mobile Military Standards 810 C, D, & E						
Applicable MIL-STD	810C		810D		810E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temperature	501.1	1,2	501.2	1,2	501.3	1,2
Low Temperature	502.1	2	502.2	1,2	502.3	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	2	506.2	2	506.3	2
Humidity	507.1	2	507.2	2,3	507.3	3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8,10	514.3	1	514.4	1
Shock	516.2	1,2,5	516.3	1	516.4	1

Receiver		
Specification	VHF	UHF
Sensitivity (12dB SINAD): (ETS)	0.3OpV (0.22 pV Typical)	
Intermodulation: (ETS)	>65 dB	
Adjacent Channel Selectivity: (ETS)	80dB @ 25KHz 75dB @ 20 kHz 65dB @ 12.5 kHz	65dB @ 12.5 kHz 70 dB @ 20 kHz 65 dB @ 12.5 kHz
Spurious Rejection: (ETS)	80 dB @ 20/25 kHz 75 dB @ 20/25 kHz	75dB @ 12.5 kHz 70 dB @ 12.5 kHz
Rated Audio: (ETS)	3W Internal 7.5W & 13W External	
Audio Distortion @ Rated Audio:	3% Typical Audio	
Hum and Noise:	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz	
Audio Response: (300 to 3000Hz)	+1, -3dB	
Conducted Spurious Emission per FCC Part 15:	57 dBm <1GHz 47 dBm >1 GHz	

*Availability subject to individual country's law and regulations.

Specifications are subject to change without notice and are issued for guidance purposes only.

All specifications listed are typical. Radios meet applicable regulatory requirements.

Conforms to EC directive 89/336/EEC

Complies with ETS 300 113

Contact your local Authorised Motorola Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.



The Exporter Cc

Specialising in the Export of Communication Equipment

PO Box 3643 Tel: +27 (0)21 851 1700
Somerset West Fax: +27 (0)21 851 1699
7129 Skype: "radioexport"
South Africa Email: exportdc@iafrica.com

www.radioexport.com

For exceptional performance, reliability and quality, Motorola Original accessories are the only options.
For full details, please refer to the Professional Radio Series Accessories brochure.



Motorola, Professional Radios,
As Dedicated As You Are and
X-Pand are trademarks of Motorola Inc.
© 2000 Motorola, Printed in the United Kingdom
<http://www.mot.com>